

SECURE MEMORY AND PROCESSING SYSTEM HAVING LASER-
SCRIBED ENCRYPTION KEY

Field of the Invention

5

This invention relates in general to the field of
secure processing systems and in particular to
processing systems with secure memory. The present
invention also relates to wireless communication
10 devices.

Background of the Invention

Security is becoming a critical feature in
15 processor and communication system designs today. It
is becoming more important to be able to store non-
volatile sensitive information within a product and
protect this information from disclosure and/or
modification. It is preferable to store this sensitive
20 information where no external access to this data is
possible. Unfortunately, it is difficult to combine
technologies to accomplish this. For example, flash
memory, EEPROM and fast logic devices are not easily
manufactured on the same die due to incompatible
25 process requirements or high cost.

Many portable communication devices provide
connectivity to networks such as the internet. This
connectivity may permit a user to purchase items over
the internet using their portable communication device,
30 but because many of these devices are relatively small
and have very limited man-Machine interfaces, it is
difficult to enter credit card information or other
authenticating information using these portable
communication devices. In addition, the Internet
35 providers desire to make the purchasing of products on-
line as simple and as pleasurable as possible.

5 is also needed are a method and system that securely stores user authentication information and other sensitive information so that it cannot be easily extracted from the portable communication device, copied to another device, or modified.

10 What is also needed are a processing system and
secure memory device that stores sensitive information
in a way that it is not easily accessible. What is
also needed is a method for storing and using sensitive
information within processing systems and communication
15 devices. What is also needed is a method for
communicating sensitive information over a non-secure
channel such as the internet.

Brief Description of the Drawings

FIG. 1 is a simplified block diagram of a communication device with a secure processing system in accordance with the preferred embodiments of the present invention;

FIG. 2 is a simplified procedure for loading sensitive information in accordance with the preferred embodiments of the present invention; and

FIG. 3 is a simplified procedure for using sensitive information in accordance with the preferred embodiments of the present invention.

Detailed Description of the Drawings

The present invention provides, among other things, a secure processing system for use in various types of communication devices. The secure processing system includes a host processor and a secure memory which provides for the storage of sensitive data in encrypted form in a storage medium external to the secure processing system. When needed by the host processor, the encrypted data is decrypted with encryption logic circuitry within the secure memory and transferred to a zeroizable memory for use by the host processor. The secure memory uses a laser-scribed encryption key coupled to encryption logic circuitry within the secure memory for encrypting and decrypting sensitive information. The laser-scribed encryption key is desirably unique to each device. In accordance with the present invention, the laser-scribed encryption key is generated by laser-scribing a semiconductor die during fabrication. The present invention includes other methods of generating the laser-scribed encryption key including, for example, burning on-time programmable fuses on a die.

The laser-scribed encryption key provides a master key used to protect sensitive data that is stored in a user's product. For example, such sensitive user data may include a user's social security number, credit
5 card number, social security service keys or an ID used for secure digital initiatives, such as digital rights management. Sensitive data may also include application source code such as game software. Preferably only certain applications within the system
10 will need to access this sensitive information.

FIG. 1 is a simplified block diagram of a communication device with a secure processing system in accordance with the preferred embodiments of the present invention. Communication device 10 is
15 comprised of a secure processing system 14 having an associated external memory 12 and other communication components 13. Device 10 may, for example, be a wireless communication device, such as a cellular or wireless phone, or a wireline communication device such
20 as a computer, or a portion thereof. Communication components 13 provide for the functionality not described in detail in FIG. 1 for either a wireless or wireline communication device, and for either communicating voice, data or video. Secure processing
25 system 14 is comprised of a host processor 16, secure memory 20, bus 18 coupling the host processor and the secure memory and on-chip system components 15. In accordance with the preferred embodiment of the present invention, host processor 16, on-chip system components
30 15 and secure memory 20 are fabricated on a single integrated circuit chip and is preferably separate from external memory 12 and other communication components 13. Host processor 16 may be one or more processing elements and is preferably the main controller for
35 secure processing system 14. Preferably, processor 16 is a digital signal processor (DSP) or a micro-controller. On-chip system components 15 comprise

other system processors, memory and other functional elements that are part of communication device 10 to allow for wireless or wireline communication of video, data and/or voice.

5 Secure memory 20 is coupled to the host processor 16 by data bus 18 and comprises a plurality of blocking gates 22 that are coupled to data bus 18. Secure memory 20 also includes laser-scribed encryption key 21 coupled to blocking gates 22. Secure memory also
10 comprises encryption logic circuitry 23 and zeroizable memory 24. Encryption logic circuitry 23 preferably implements a symmetric encryption algorithm using laser-scribed encryption key 21. Zeroizable memory 24 is preferably a random access memory (RAM) having
15 zeroizing input 28. Zeroizable memory 24 may be coupled to either to encryption logic circuitry 23 or data bus 18. The contents of zeroizable memory 24 are erased, for example by causing the contents to be set to a fixed value such as zero or another predetermined
20 value when a zeroized signal is received at zeroizing input 28. System monitor 25, for example, sends the zeroizing signal to zeroizable memory 24 upon the occurrence of any one of several predetermined conditions. Such conditions may include, for example,
25 a detection of inappropriate access to the secure information in zeroizable memory 24 or the completion of an operation where the secure data in the zeroizable RAM is no longer needed. Furthermore, the zeroized signal preferably causes the encryption algorithm
30 embedded within an encryption logic circuitry 23 to be reset and further causes blocking gates 22 to prevent access to laser-scribed encryption key 21 by encryption logic circuitry 23 and zeroizable memory 24.

35 In accordance with the preferred embodiment of the present invention, the blocking gates 22 are comprised of logic "AND" gates which, when activated by a blocking control signal, prevent access to (e.g.,

secure memory 20 when for example software debug capability is being utilized.

Secure memory 20 includes system monitor 25 functions to help ensure the proper operation of secure memory 20. For example, improper attempts to access laser-scribed encryption key 21 or memory 24 are detected by the system monitor 25. Preferably, system monitor 25 monitors the sequence of events at power-up and when a power-up test is not completed successfully, system monitor 25 desirably prevents access to the secure memory components. In addition, system monitor 25 monitors activity on system debug port 29. Attempts to enable the debug capability of the system are detected by the system monitor 25. When system monitor 25 detects an unauthorized condition, blocking gates 22 are enabled to disable access to encryption logic circuitry 23 and zeroizable memory 24 and prevent the encryption logic circuitry 23 from accessing laser-scribed encryption key 21. In addition, system monitor 25 provides an assertion signal on zeroizing input 28 to zeroizable memory 24 to erase any information that has been stored therein.

In accordance with the preferred embodiment of the present invention, secure memory 20 is tested by self-test element 26 when secure processing system 14 is powered up. These tests, among other things, verify the proper operation of encryption logic circuitry 23, zeroizable memory 24, zeroizing input 28, and blocking gates 22. In addition, the ability of system monitor 25 to disable access to the secure memory is preferably also verified by self-test element 26 when secure processing system 14 is powered up. If any test fails, secure memory 20 is disabled.

In accordance with one embodiment of the present invention, communication device 10 contemplates having secret keys stored in non-secure external memory 12 in encrypted form, each secret key having been encrypted

with laser-scribed encryption key 21 using secure processing system 14. When needed, communication device decrypts one of the secret keys with encryption logic circuitry 23 using laser-scribed encryption key 21, and stores the decrypted secret key in zeroizable memory 24. The decrypted secret key may be used by host processor 16 in any number of ways, including, for communications with other communication devices.

In one embodiment of the present invention, the decrypted secret key may be the user's private key which is part of a public/private key pair. In this embodiment for example, the user's private key may be used for authentication of digital signatures as well as decryption of data.

In another embodiment of the present invention, the secret key may be secret information used to generate a common session key with another communication device. The secret key may also be the common session key used to subsequently communicate secured information. In any of these embodiments of the present invention, secure data or secure voice or video may be communicated either over wireless or wireline networks. Communication components 13 and other on-chip system components 15 are suitably configured by those of ordinary skill in the art. Communication components 13, may include, for example, vocoders, transceivers, amplifiers, processors, etc.

It should be noted that, although various embodiments are disclosed herein, the present invention is equally suitable for the safeguarding and use of any sensitive information. Other embodiments are described below.

In another preferred embodiment, the present invention provides for a method of purchasing items over a non-secure communication link, such as the internet, for example using a secure communication device such as communication device 10 of FIG. 1.

004260" 646T 2960

In accordance with this embodiment of the present invention, a secure memory embedded in the Host processor is used to secure the user's sensitive information. The user of the portable communication device enter sensitive information such as a credit card numbers and other authentication information into the device. This can be done prior to any use of this information and may be performed using the device's keypad and display or it may involve downloading information from a computer, a network or wireless link.

Once the host processor is loaded with this sensitive information, the host processor uses the secure memory to encrypt the sensitive information using the laser-scribed encryption key. After encryption, the encrypted sensitive information is stored in a non-secure memory. The encrypted sensitive information does not need to be protected because this information can only be decrypted and used by the secure memory containing the laser-scribed encryption key that originally encrypted it.

The communication device may also be loaded with a digital certificate or public key used to establish a secure communication session with an internet vendor. Like the users of credit card information, the digital certificate may be encrypted by the secure memory using the laser-scribed encryption key and stored in non-secure memory.

In one embodiment of the present invention, an additional step for loading the communication device is to establish a personal identification number (PIN) for use in accessing control to the device. As with the credit card information, the PIN is loaded into the device, encrypted by the secure memory using the laser-scribed encryption key and stored in non-secure memory.

In an alternate embodiment of the present invention, an additional step for loading the

communication device is to establish biometric information for use in accessing control to the device. As with the credit card information, the user's biometric information is loaded into the device, encrypted by the secure memory using the laser-scribed encryption key and stored in non-secure memory. In accordance with this alternative embodiment, the communication device preferably comprises components for receiving the user's biometric data. Examples of these biometric reception components include retinal scan components, fingerprint reading components, voice print identification components, and speaker identification and verification components.

In order to complete a transaction the user either enter the PIN, or provided biometric data to the biometric reception circuitry. This step, for example, helps protect the communication device from misuse in the event that the device is lost or stolen. Once the PIN is entered or the biometric data is received, the encrypted PIN or biometric data is retrieved from non-secure memory and decrypted by the secure memory using the laser-scribed encryption key. The decrypted PIN or biometric data is compared to the entered PIN or received biometric data and the transaction continues where the information matches.

The communication device then sends the encrypted certificate to the secure memory where it is decrypted using the laser-scribed encryption key. The host processor uses this certificate to establish a secure session with, for example, an internet vendor. Secure Socket Layer (SSL), for example, is a standard technique used in the internet community to establish such a session.

Once the secure session is established, the host processor sends the encrypted credit card and authentication information to the secure memory where it is decrypted using the laser-scribed encryption key.

After decryption the host processor sends the decrypted sensitive information to a recipient such as an internet vendor through the secure session previously established.

5 One of the advantages of the present invention is that the sensitive information is never accessible outside of the host processor and the Secure Memory after it is originally loaded. In the preferred embodiment of the present invention, the secure memory
10 and the host processor are on the same chip. In this case the sensitive information is never available outside of this chip, thus protecting the information from any external attempt to intercept it.

Another advantage of the present invention is that
15 the user action during the purchase session is primarily only the entering of the PIN or providing the biometric information. The other steps for the secure transaction are automatic and occur without the knowledge or direction of the user.

20 Accordingly, user interaction is simplified during an internet purchase and the information required for on-line transactions is stored in a secure manner for multiple purchase sessions.

In accordance with other embodiments of the
25 present invention, the present invention provides a method for transferring sensitive data over non-secure communication channels using the secure communication device of the present invention. The secure communication device includes a host processor, a
30 secure memory that includes the laser-scribed encryption key, a non-secure memory for storing sensitive data in encrypted form; the sensitive data being previously encrypted with the laser-scribed encryption key.

35 FIG. 2 is a simplified procedure for loading sensitive information in accordance with the preferred embodiments of the present invention. Processing

system 14 (FIG. 1), for example, is suitable for performing procedure 200, although other processing systems may be suitable.

Sensitive data or sensitive information is loaded
5 into the processing system or device in step 202. This information may be loaded directly through a keypad or another external interface. The keypad may be an attached keypad and be a part of communication components 13 (FIG. 1). The information may also be
10 loaded over a communication link, for example, via the communication components 13 (FIG. 1). In one embodiment, the information is loaded in a plain text form while another embodiment, the information is loaded in encrypted form and host processor 16 (FIG.
15 1), for example, may first decrypt the information prior to re-encrypting using secure memory 20 and storing it in external memory 12.

Once the sensitive information is loaded, the blocking gates, such as blocking gates 22 (FIG. 1) are
20 disabled in step 204. Disabling the blocking gates permits the host processor to access the encryption logic circuitry and the zeroizable memory within the secure memory. Disabling the blocking gates also enables the encryption logic circuitry to access the
25 laser-scribed encryption key 21 (FIG. 1). The host processor preferably never has direct access to the laser-scribed encryption key, even, for example, when the blocking gates are disabled.

In step 206, the host processor sends the
30 sensitive information through the encryption logic. In this step, the sensitive information is encrypted with the laser-scribed encryption key by encryption logic circuitry and stored in a memory internal to the secure memory device, and preferably stored in a zeroizable
35 RAM. The sensitive information is now encrypted with a key that is preferably only known by the secure memory

and this key can not be readily extracted from the secure memory.

In step 208, the host processor reads the encrypted sensitive information from the zeroizable memory and stores this information in a memory that is preferably external to the secure memory such as external memory 12 (FIG. 1). Physical protection of the external memory may not be necessary because the encrypted version of the sensitive information is stored in the external memory while the key to decrypt the sensitive information (i.e., the laser scribed encryption key) is kept within the secure memory.

In step 210, the host processor enables the blocking gates to disable access to the encryption logic circuitry and the zeroizable memory and prevent the encryption logic from accessing the laser scribed encryption key. In step 214, a zeroize input signal, such as zeroizing input 28 (FIG. 1) is provided to the zeroizable memory to erase any information that was temporarily stored in the zeroizable memory.

FIG. 3 is a simplified procedure for using sensitive information in accordance with the preferred embodiments of the present invention. This information, for example, may have been loaded in procedure 200 (FIG. 2). Processing system 14 (FIG. 1), for example, is suitable for performing procedure 300, although other processing systems may be suitable. Procedure 300 is executed when the host processor requires use the sensitive information that is stored in encrypted form.

In step 302, the blocking gates are disabled to allow the host processor to access the secure memory. Disabling the blocking gates permits the host processor to access the encryption logic circuitry and the zeroizable RAM within, for example, secure memory 20 (FIG. 1). It also enables the encryption logic circuitry access to the laser-scribed encryption key.

The host processor desirably never has direct access to the laser-scribed encryption key, even when the blocking gates are disabled.

Once access to the secure memory is enabled, in
5 step 304 the host processor reads the encrypted
sensitive information , for example from external
memory 12 (FIG. 1) and writes this information to the
encryption logic circuitry. In step 306, the
10 encryption logic circuitry decrypts the encrypted
sensitive information using the laser-scribed
encryption key. In step 308, the decrypted sensitive
information is stored within the secure memory,
preferably in zeroizable memory 24 (FIG. 1).

In step 310, the host processor uses the sensitive
15 information for whatever purpose the information is
needed for. The sensitive information remains in the
zeroizable memory until the host processor causes the
information to be erased. Also, an external event, may
also cause the information to be erased. Erasing the
20 information in the zeroizable memory is accomplished,
for example, by the assertion of the zeroize input
(e.g. input 28 FIG. 1) of the zeroizable memory.
Examples of external events which cause erasure of the
zeroizable memory include the systems detection of
25 tampering or detection of an unauthorized condition,
for example by system monitor 25 (FIG. 1) or debug
detector 27 (FIG. 1). The host processor may access
the sensitive information as often as needed while the
information remains in zeroizable memory.

30 In step 312, the sensitive information that is
temporarily stored in the zeroizable memory is erased.
This is accomplished by the host processor overwriting
the information stored in the secure memory or by
activating or asserting a zeroize input to the
35 zeroizable memory. In accordance with this embodiment
of the present invention, there is no need to re-
encrypt the sensitive information or store this

information back into external memory because preferably, the original encrypted sensitive information is not removed from external memory and is still contained within the external memory to be used
5 next time the host processor requires access to the sensitive information.

When the host processor no longer desires access to the sensitive information in the zeroizable memory, in step 314 the host processor enables the blocking
10 gates to disable access to the encryption logic circuitry and the zeroizable memory, and prevents the encryption logic circuitry from accessing the laser scribed encryption key.

Thus, a secure memory and secure processing system
15 for use in various types of communication devices has been described which overcomes specific problems and accomplishes certain advantages relative to prior art methods and mechanisms. The improvements over known technology are significant.

20 The foregoing description of the specific embodiments will so fully reveal the general nature of the invention that others can, by applying current knowledge, readily modify and/or adapt for various applications such specific embodiments without
25 departing from the generic concept, and therefore such adaptations and modifications should and are intended to be comprehended within the meaning and range of equivalents of the disclosed embodiments.

It is to be understood that the phraseology or
30 terminology employed herein is for the purpose of description and not of limitation. Accordingly, the invention is intended to embrace all such alternatives, modifications, equivalents and variations as fall within the spirit and broad scope of the appended
35 claims.